



NEW

## ZC SERIES

1000 / 2000 / 3000 / 4000 / 5000 / 6000

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 高强度复合材料主体、主盖、线轮座  
High strength composite material body, spool cover and spool seat
- 无间隙单向系统, 4个精密轴承  
Infinite anti-reverse system, 4 high quality bearings
- 防缠线及回转平衡设计线轮座  
Spool seat designed by prevent tangling and rotary balance system
- 精密防腐铝合金线轮, 双色氧化  
Precision forged aluminum and double anodized spool with corrosion protection
- 左右手互换, 高强度铝精加工摇臂  
Interchangeable, high-strength CNC machined handle



型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
ZC1000	4+1	Y	61	5.2:1	5	0.15/200 0.18/180 0.2/150
ZC2000	4+1	Y	64	5.2:1	6	0.18/240 0.2/200 0.25/140
ZC3000	4+1	Y	70	5.2:1	6	0.2/240 0.25/200 0.3/140
ZC4000	4+1	Y	78	5.2:1	6	0.3/200 0.35/160 0.4/120
ZC5000	4+1	Y	85	5.2:1	8	0.35/200 0.4/160 0.45/120
ZC6000	4+1	Y	90	5.2:1	8	0.35/270 0.4/210 0.5/130

NEW

## ZC SERIES

1000X / 2000X / 3000X / 4000X / 5000X / 6000X

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 高强度复合材料主体、主盖、线轮座  
High strength composite material body, spool cover and spool seat
- 防缠线及回转平衡设计线轮座  
Spool seat designed by prevent tangling and rotary balance system
- 精密防腐铝合金线轮, 双色氧化  
Precision forged aluminum and double anodized spool with corrosion protection
- 左右手互换, 可折叠摇臂  
Interchangeable folded handle



型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
ZC1000X	1	N	61	5.2:1	5	0.15/200 0.18/180 0.2/150
ZC2000X	1	N	64	5.2:1	6	0.18/240 0.2/200 0.25/140
ZC3000X	1	N	70	5.2:1	6	0.2/240 0.25/200 0.3/140
ZC4000X	1	N	78	5.2:1	6	0.3/200 0.35/160 0.4/120
ZC5000X	1	N	85	5.2:1	8	0.35/200 0.4/160 0.45/120
ZC6000X	1	N	90	5.2:1	8	0.35/270 0.4/210 0.5/130



NEW

## ZC SERIES

1000N / 2000N / 3000N / 4000N / 5000N / 6000N

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 高强度复合材料主体、主盖、线轮座  
High strength composite material body, spool cover and spool seat
- 无逆止开关, 无间隙单向系统, 4个精密轴承  
Always on, infinite anti-reverse system, 4 high quality bearings
- 防缠线及回转平衡设计线轮座  
Spool seat designed by prevent tangling and rotary balance system
- 精密防腐铝合金线轮, 双色氧化  
Precision forged aluminum and double anodized spool with corrosion protection
- 左右手互换, 高强度铝精加工摇臂  
Interchangeable, high-strength CNC machined handle



型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
ZC1000N	4+1	Y	61	5.2:1	5	0.15/200 0.18/180 0.2/150
ZC2000N	4+1	Y	64	5.2:1	6	0.18/240 0.2/200 0.25/140
ZC3000N	4+1	Y	70	5.2:1	6	0.2/240 0.25/200 0.3/140
ZC4000N	4+1	Y	78	5.2:1	6	0.3/200 0.35/160 0.4/120
ZC5000N	4+1	Y	85	5.2:1	8	0.35/200 0.4/160 0.45/120
ZC6000N	4+1	Y	90	5.2:1	8	0.35/270 0.4/210 0.5/130

NEW

## ZC SERIES

9000 / 10000 / 11000 / 12000

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 高强度复合材料主体、主盖、线轮座  
High strength composite material body, spool cover and spool seat
- 无间隙单向系统, 8个精密轴承  
Infinite anti-reverse system, 4 high quality bearings
- 防缠线及回转平衡设计线轮座  
Spool seat designed by prevent tangling and rotary balance system
- 精密防腐铝合金线轮, 双色氧化  
Precision forged aluminum and double anodized spool with corrosion protection
- 左右手互换, 高强度铝精加工摇臂  
Interchangeable, high-strength CNC machined handle
- 长绕线行程, 不锈钢双螺旋导杆往复排线系统  
Long winding distance, stainless steel double spiral worm shaft reciprocating wire system



型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
ZC9000	8+1	Y	90	4.1:1	30	0.3/150 0.5/100
ZC10000	8+1	Y	90	4.1:1	30	0.3/320 0.5/190
ZC11000	8+1	Y	90	4.1:1	30	0.4/330 0.55/240
ZC12000	8+1	Y	90	4.1:1	30	0.4/350 0.55/260

NEW

## ZD SERIES

1000SH/1000H/2000SH/2000H/3000SH/3000H/4000SH/4000H

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 高强度复合材料主体、主盖、线轮座  
High strength composite material body, spool cover and spool seat
- 无间隙单向系统, 4个精密轴承  
Infinite anti-reverse system, 4 high quality bearings
- 防缠线及回转平衡设计线轮座  
Spool seat designed by prevent tangling and rotary balance system
- 精密防腐铝合金线轮, 双色氧化  
Precision forged aluminum and double anodized spool with corrosion protection
- 左右手互换, 高强度铝精加工摇臂  
Interchangeable, high-strength CNC machined handle
- 高速比齿轮设计  
High gear ratio design

型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
ZD1000SH	4+1	Y	73	6.2:1	5	0.10/190 0.12/150
ZD1000H	4+1	Y	73	6.2:1	5	0.14/200 0.16/160
ZD2000SH	4+1	Y	76	6.2:1	5	0.12/170 0.14/150
ZD2000H	4+1	Y	76	6.2:1	5	0.16/180 0.20/140
ZD3000SH	4+1	Y	83	6.2:1	8	0.14/180 0.16/150
ZD3000H	4+1	Y	83	6.2:1	8	0.20/290 0.24/260
ZD4000SH	4+1	Y	93	6.2:1	8	0.16/160 0.20/140
ZD4000H	4+1	Y	93	6.2:1	8	0.24/280 0.26/260



NEW

## ZD SERIES

1000S/1000/2000S/2000/3000S/3000/4000S/4000

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 高强度复合材料主体、主盖、线轮座  
High strength composite material body, spool cover and spool seat
- 无间隙单向系统, 4个精密轴承  
Infinite anti-reverse system, 4 high quality bearings
- 防缠线及回转平衡设计线轮座  
Spool seat designed by prevent tangling and rotary balance system
- 精密防腐铝合金线轮, 双色氧化  
Precision forged aluminum and double anodized spool with corrosion protection
- 左右手互换, 高强度铝精加工摇臂  
Interchangeable, high-strength CNC machined handle

型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
ZD1000S	4+1	Y	61	5.2:1	5	0.10/190 0.12/150
ZD1000	4+1	Y	61	5.2:1	5	0.14/200 0.16/160
ZD2000S	4+1	Y	64	5.2:1	5	0.12/170 0.14/150
ZD2000	4+1	Y	64	5.2:1	5	0.16/180 0.20/140
ZD3000S	4+1	Y	70	5.2:1	8	0.14/180 0.16/150
ZD3000	4+1	Y	70	5.2:1	8	0.20/290 0.24/260
ZD4000S	4+1	Y	78	5.2:1	8	0.16/160 0.20/140
ZD4000	4+1	Y	78	5.2:1	8	0.24/280 0.26/260



NEW

## BMA SERIES

300/300L

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 锻造铝合金全机加工主体、主体盖和线轮  
Forged aluminum alloy all CNC machined body, spool cover and spool
- 铝合金阳极氧化表面处理  
Aluminum alloy with anodized surface treatment
- 无间隙单向系统, 8个精密不锈钢轴承  
Infinite anti-reverse system, 8 high quality stainless steel bearings
- 精准抛投磁力阻尼系统  
Precision magnetic casting system

型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
BMA300	8+1	Y	73	6.3:1	8	0.2/240 0.25/180 0.30/130
BMA300L	8+1	Y	73	6.3:1	8	0.2/240 0.25/180 0.30/130



# JINAN PELICAN TRD.CO.,LTD



**NEW**

## MBC SERIES

1510 / 1510L / 1510H / 1510HL / 1510XH / 1510XHL

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 高强度复合材料主体、主盖、线轮座  
High strength composite material body, spool cover and spool seat
- 无间隙单向系统, 6个精密不锈钢轴承  
Infinite anti-reverse system, 6 high quality stainless steel bearings
- 精准抛投磁力阻尼系统  
Precision magnetic casting system
- 精密防腐铝合金线轮  
Precision forged aluminum spool with corrosion protection
- 侧盖快速拆卸设计  
Quick disassembly side cover
- 多种齿数比, 满足各种需求  
Multiple gear ratio selection
- 3组碳纤维板刹车华司  
3 sets of carbon break pads

型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
MBC1510	6+1	Y	66	6.5:1	8	0.2/230 0.25/145 0.30/105
MBC1510L	6+1	Y	66	6.5:1	8	0.2/230 0.25/145 0.30/105
MBC1510H	6+1	Y	72	7.1:1	8	0.2/230 0.25/145 0.30/105
MBC1510HL	6+1	Y	72	7.1:1	8	0.2/230 0.25/145 0.30/105
MBC1510XH	6+1	Y	81	8.0:1	8	0.2/230 0.25/145 0.30/105
MBC1510XHL	6+1	Y	81	8.0:1	8	0.2/230 0.25/145 0.30/105



**NEW**

## GBC SERIES

1510 / 1510L / 1510H / 1510HL / 1510XH / 1510XHL

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 铝合金主体, 加工中心一次装夹加工成型  
Aluminum alloy body made by an accurate working under extremely high precision machining center
- 无间隙单向系统, 6个精密不锈钢轴承  
Infinite anti-reverse system, 6 high quality stainless steel bearings
- 精准抛投磁力阻尼系统  
Precision magnetic casting system
- 精密防腐铝合金线轮  
Precision forged aluminum spool with corrosion protection
- 侧盖快速拆卸设计  
Quick disassembly side cover
- 多种齿数比, 满足各种需求  
Multiple gear ratio selection
- 3组碳纤维板刹车华司  
3 sets of carbon break pads

型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity (mm/m)
GBC1510	6+1	Y	73	6.5:1	8	0.2/200 0.25/135 0.30/100
GBC1510L	6+1	Y	73	6.5:1	8	0.2/200 0.25/135 0.30/100
GBC1510H	6+1	Y	80	7.1:1	8	0.2/200 0.25/135 0.30/100
GBC1510HL	6+1	Y	80	7.1:1	8	0.2/200 0.25/135 0.30/100
GBC1510XH	6+1	Y	90	8.0:1	8	0.2/200 0.25/135 0.30/100
GBC1510XHL	6+1	Y	90	8.0:1	8	0.2/200 0.25/135 0.30/100





NEW

## MCH SERIES

65/65L

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 锻造铝合金全机加工主体、主体盖和线轮  
Forged aluminum alloy all CNC machined body, spool cover and spool
- 铝合金阳极氧化表面处理  
Aluminum alloy with anodized surface treatment
- 无间隙单向系统, 8个精密不锈钢轴承  
Infinite anti-reverse system, 8 high quality stainless steel bearings



型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity
MCH65	8+1	Y	96	4.7:1	2	3#/100
MCH65L	8+1	Y	96	4.7:1	2	3#/100

NEW

## FFD SERIES

65/65L

### PRODUCT INTRODUCTION

- 新颖时尚的外观造型设计  
Novel and fashionable appearance design
- 锻造铝合金全机加工主体、主体盖和线轮  
Forged aluminum alloy all CNC machined body, spool cover and spool
- 铝合金阳极氧化表面处理  
Aluminum alloy with anodized surface treatment
- 无间隙单向系统, 7个精密不锈钢轴承  
Infinite anti-reverse system, 7 high quality stainless steel bearings



型号 Item	轴承数 Ball bearing	单向轴承 One-way	最大卷取长度 Line per handle turn(cm)	齿数比 Gear ratio	最大刹车力 Max drag(kg)	线容量 Line capacity
FFD65	7+1	Y	73	3.6:1	2	3#/100
FFD65L	7+1	Y	73	3.6:1	2	3#/100